



Dalo model bollard built with an iron tube with a diameter of \varnothing 95 or 200 mm. and 2.5 mm. of thickness. With 8 mm stainless steel top cap.

STANDARD FINISHES:

Glossy finish cover:

Grey oxiron \varnothing 95. Ref. PDALOGIB

Grey oxiron \varnothing 200 Ref. PDALOGIB02

Matte finish cover:

Grey oxiron \varnothing 95. Ref. PDALOGIM

Grey oxiron \varnothing 200 Ref. PDALOGIM02

OPTIONAL:

- Plate for bollard \varnothing 95. Ref. SUPP
- Plate for bollard \varnothing 200 / 220. Ref. SUPP2
- Customization with logo engraving.
- Other colors to consult.
- Possibility of manufacturing in imitation corten or in other colors (according to Ral letter).

ACCESSORIES:

- 1 ring for bollard. Ref. S1AP
- 2 rings for bollard. Ref. S2AP
- Galvanized chain of \varnothing 6 mm. Ref. CG6100
- 40mm brass padlock. with steel arch. Ref. CNMCAD40

DALO FIXED BOLLARD:

Diameter: \varnothing 95 / 220 mm.
Visible height: 800 mm.
Total height: 1000 mm.
Thickness: 2.5 mm.

DALO FIXED WITH PLATE:

Diameter: \varnothing 95 / 220 mm.
Visible / total height: 800 mm.
Thickness: 2.5 mm.

